

Location Name		Date	
Street Address		Install Company	
State, Zip code		Installers Phone #	
Contact Name		Installer Name	
Phone		Installer Email	
Email		Additional Info	

	Model Number	Serial Number
1		
2		

Physical Dimensions, Weight and Gas Rating

Electric Models	Height (in/cm)	Width (in/cm)	Depth (in/cm)	Weight (lbs/kg)	
611	32.6 / 85.80	36.7 / 93.22	32.3 / 82.04	265 / 120.20	
621	33.1 / 84.07	44.1 / 112.01	39.3 / 99.82	342 / 155.13	
623	23.7 / 60.20	26.9 / 68.33	23.1 / 58.67	146 / 66.225	
1011	42.8 / 108.71	36.7 / 93.22	32.3 / 82.04	324 / 146.96	
1221	52.9 / 134.37	43.7 / 110.99	37.8 / 96.01	582 / 263.99	
2011	73.1 / 185.67	37.3 / 94.74	32.8 / 83.31	624 / 283.04	
2021	71.5 / 181.61	45.5 / 115.57	37.9 / 96.27	774 / 351.08	
Gas Models	Height (in/cm)	Width (in/cm)	Depth (in/cm)	Weight (lbs)	BTU
611	32.6 / 85.80	36.7 / 93.22	32.3 / 82.04	288 / 130.64	46,000
621	33.1 / 84.07	44.1 / 112.01	39.3 / 99.82	373 / 175.99	99,000
1011	42.8 / 108.71	36.7 / 93.22	32.3 / 82.04	343 / 155.58	80,000
1221	52.9 / 134.37	43.7 / 110.99	37.8 / 96.01	618 / 243.13	160,000
2011	73.1 / 185.67	37.3 / 94.74	32.8 / 83.31	671 / 261.27	160,000
2021	71.5 / 181.61	45.5 / 115.57	37.9 / 96.27	876 / 338.38	280,000

Installation Clearances

	Y	N
Door Clearance?		
Elevator Clearance?		
Hallway Clearance?		

Check all doors, entryways and hallways from delivery point to installation area. Verify proper clearances on all sides of oven at installation point. Indicate sufficient clearance on table to right.

Spec sheets with dimensional information can be found Online at AccuTemp.net or in the installation manual.

Operation Clearances

CAUTION:

- Minimum distance from a non-heat source: 2 inches (10 cm)
- Minimum distance from a heat source (i.e. stove, griddle, fryer, kettle, skillet): 20 inches (50 cm)
- Minimum distance above equipment: 30 inches (80 cm)

Site Verification Form

Water Supply

TWO (2) TOTAL COLD WATER INLETS: Drinking Quality
ONE (1) TREATED WATER INLET: BSPP to 3/8" hose
ONE (1) UNTREATED WATER INLET: BSPP to 3/8" hose
WATER DRAIN: 2" Connection (MDL 623 has a 1.5 inch drain connection)

Model	Gallons Per Day/ Liters Per Day (GPD/LPD)
623	19 / 71
611	32 / 121
1011	44 / 166
1221	63 / 238
2011	63 / 238
2021	101 / 382

*Daily water usage values are based on this duty cycle: 4 hours of steam, 1 rinse cycle, 4 more hours of steam, 1 extra strong wash cycle.
 *Actual consumption may vary depending on use.

Water Quality Requirements

It is the sole responsibility of the owner/operator/purchaser of this equipment to verify that the incoming water supply is comprehensively tested and if required, a means of "water treatment" must be provided that would meet compliance requirements with the water quality standards published below. Non-compliance with these minimum standards could potentially damage this equipment and/or components and VOID the original equipment manufacturer's warranty.

Description	Value
Inlet Pressure	50 - psi
Free Chlorine	< 0.1 ppm (mg/l)
Total Chlorine	< 0.1 ppm (mg/l)
pH	7.0 - 8.5
Total Dissolved Solids (TDS)	<150 ppm (mg/l)
Water Hardness	< 90 ppm (mg/l)
Alkalinity (as CaC3)	< 60 ppm (mg/l)
Chlorides (Sulfate+Chloride+Nitrate)	< 40 ppm (mg/l)
Iron FE	< 0.1 ppm (mg/l)
Silica	< 13 ppm (mg/l)

Drain

CAUTION

- Unit should be placed on level floor.
- Minimum distance from Floor Drain: 20 in / 50.8cm
- Floor Drain must not be directly under the equipment.
- Recommend a 6ft distance to drain
- Minimum drain pipe length must Models 623, 611 & 1011: 20 in / 50.8cm
- Minimum drain pipe length for Models 2011, 1221 & 2021: 40 in / 101.6cm
- Use 2 in drain pipe for all combi ovens except the 623 which uses a 1.5 in drain pipe.
- **The drain line should have a descending slope. Verify 1/4" (in) slope to 1' (ft) of drain line.**

	√
Water supply within spec?	

Verify Adequate Supply:	√
Voltage	
Amperage	
Phase	

Electric Supply Requirements

Circuit protection reference chart (required breaker amperage)

	0623	0611	0621	1011	1221	2011	2021
208v 1Ø	20	45	-	-	-	-	-
240v 1Ø	25	50	-	-	-	-	-
208v 3Ø	15	25	50	45	80	90	150
240v 3Ø	15	30	50	50	90	100	175
480v 3Ø	10	15	30	25	45	45	80
	-	0611	0621	1011	1221	2011	2021
120v 1Ø *	-	10	10	10	20	20	20
240v 1Ø *	-	10	10	10	10	10	16

Note: Shaded box indicates a pig tail cord option is available from the factory

Gas Models Electric Models

AccuTemp Products, Inc.'s appliances have been tested by Underwriters Laboratories (UL) to the NFPA 70 – National Electric Code (NEC) and the UL Standard for Safety for Commercial Electric Cooking Appliances (UL 197) to qualify our equipment as non-continuous loads, with respect to the NEC definition of continuous load and UL 197, Sections 28.1.4 and 48.1. This classification does not require installers to use an overcurrent protection device rated at 125% of the appliance current rating, with respect to NEC, Article 210.20 and UL 197, Section 17.1.4. With the requirement that our appliances operate on branch circuits only, the supply conductors and overcurrent protection device must have a minimum current ratings equal to or greater than the marked appliance current rating, with respect to NEC, Article 422.10.

*** Do not connect to a GFCI outlet. Hardwiring of this appliance to a dedicated 20A breaker is required.**

SIGNATURE	PRINTED NAME	POSITION	DATE:

SEND IN FORM

Please complete and fax this form to AccuTemp Products @ (260) 493-0318 or e-mail to VisionService@AccuTemp.net For technical questions please call 1-800-480-0415