

Project: _____ Location: _____ Item #: _____ Quantity: _____

Standard Features

- Kettle System-Seamless deep-drawn 304 kettle liner with an integrally formed radius lip
- 304 stainless kettle jacket
- Kettle protection system— thermostat temperature control, 150°F - 260°F, pressure relief valve, air eliminator valve, pressure gauge, jacket-water fill, automatic low water cut off and indicator light, field replaceable heating elements, tilting cut-off switch
- Full body insulation between kettle jacket and outer casing
- 304 stainless outer casing seam welded to radius lip
- 304 stainless, seam welded to control console
- 304 stainless, reinforced gear box
- Self locking worm gear tilt mechanism
- 304 stainless, 2" tubular support frame
- Adjustable flanged feet

Optional Features

- Single or dual faucet with bracket & 12" or 18" swing nozzle*
- 60" flexible spray hose assembly (vinyl or stainless) for dual or single faucet*
- Faucet bracket (ALFBT)
- Riser for table mounted fill faucet (ALRISER)
- Automatic water filling meter (ALAC-WS)
- Mixer/agitator, two speed (Call for pricing)
- Correctional Package*
- 316 Liner (AL316LNR)

* Call AccuTemp for additional information

Electrical Options

208V, 240V, 380V, 415V, 440V, 480V

Short Spec

AccuTemp Edge Series tilting floor-mounted kettle, model ALTWE-XX (20, 30, 40, or 60 gallon capacity), seamless deep-drawn 304 kettle liner with integrally formed radius lip and 304 stainless kettle jacket. Full body insulation between the kettle jacket and outer casing. 2/3 jacketed with pressure relief valve, pressure gauge, jacket-water fill valve, automatic low water cut off and indicator light and field replaceable heating elements. Seam welded control console with thermostat temperature control, 150°F to 260°F (65°C to 140°C).

Other Approvals



Accessories

- Care Kit (ALKCK-L)
- Electric timer with buzzer (ALAT)
- Pour lip pan holder assembly (ALPHKTL)
- Measuring strip (ALMS)
- Lift-off or two piece hinged*
- 1 piece actuator-assisted lid, 20-60 gal. (ALACT-M)
- Single basket 20-40 gal. (ALSBI-M)
- Tri-basket insert (ALTBI-S)
- Nylon bag insert with spreader ring (ALNBI)
- 2" or 3" draw off valve, compression or ball type fitting*

* Call AccuTemp for additional information



Model ALTWE-60
(shown with optional 1 1/2 draw-off valve)

INSULATED SELF-CONTAINED TILTING FLOOR-MOUNTED KETTLE- ALTWE

20-60 GALLON CAPACITY—Electric, 2/3 Jacketed Insulated for Safety™ Deep Drawn Construction Tilting, Floor Mounted. Made in USA

MODEL ALTWE ELECTRICAL SPECIFICATIONS (AMPERES PER LEG)

GAL	KW	208 Volt		240 Volt		380 Volt		415 Volt		440 Volt		480 Volt	
		1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø	1Ø	3Ø
20	12	57.7	33.3	50.0	28.9	31.6	18.2	28.9	16.7	27.3	15.7	25.0	14.4
30	24	115.4	66.6	100.0	57.7	63.2	36.5	57.8	33.4	54.5	31.5	50.0	28.9
40	24	115.4	66.6	100.0	57.7	63.2	36.5	57.8	33.4	54.5	31.5	50.0	28.9
60	36	173.1	99.9	150.0	86.6	94.7	54.7	86.7	50.1	81.8	47.2	75.0	43.3

MODEL ALTWE DIMENSIONS

GAL	A	B	C	D	F	G	H*	K	L	S*	W	Y
20	22.0	16.0	41.6	7.0	43.1	42.0	22.2	31.0	35.0	36	18.0	35.5
30	23.0	20.3	43.5	7.0	44.1	42.5	19.8	31.0	36.0	36	18.5	37.4
40	25.5	22.3	47.5	7.0	46.6	43.5	21.7	31.0	38.5	37.3	19.9	41.4
60	29.5	48.6	48.6	7.0	51.6	45.3	19.9	31.0	42.6	39.3	21.9	42.5

*Dimensions H & S apply only if an optional 2" draw-off is ordered. If a 3" draw-off is required, contact AccuTemp for applicable dimensions.

DRAWING REPRESENTS 60 GALLON MODEL WITH OPTIONAL 1 1/2" DRAW-OFF

